



HH Shower

Features

- 1.5 gpm flow rate. Patented vacuum booster technology compacts the water under pressure which explodes out of the showerhead 1.75 times harder than a standard shower creating a flow impact as good or better than most 2.5 gpm showers.
- Saves Water and Energy - by reducing the consumption of hot water which significantly lowers gas or electrical load. Using only 1.5 gpm saves 1 gallon per minute of water compared to standard 2.5gpm showerheads.
- Reduces Scale - as water enters the chamber, droplets are large and relatively slow-moving. Under the intense vacuum force water droplets are compacted and highly energized. As they exit the vacuum chamber the smaller droplets both expand and vibrate rapidly. This combination of vibration, smaller-sized droplets and increased velocity dramatically reduces the formation of mineral crystals (scaling) by reducing attachment sites on the front of the spray plate.
- Reduces low pressure problems - the powerful release from the vacuum chamber creates a pressure boosting effect that counters the weak flow stream that accompanies low water pressure.



Colors/Finishes

- CP Polished Chrome

Specified Model:

Model	Description	PSI
HH-1.5 -CP	1.5 gpm Hand Held shower head complete with flexible hose and arm mount.	Standard 50psi <input type="checkbox"/> Low Pressure 30psi <input type="checkbox"/> High Pressure 70psi <input type="checkbox"/>

Product Specification

Hand held shower head shall be made of ABS construction. Patented vacuum booster valve must pull a venturi vacuum of no less than 19.6 inches of Hg across its air intake orifice when attached to an operating model HH-1.5-CP. Hand Held showerhead shall be SSI model HH-1.5-CP running at __PSI