

SPECIFICATIONS

Customer Service: 1-800-460-7019
www.fluidfaucets.com

Specifications

- Heavy brass construction for durability and reliability
- Kerox 45mm ceramic cartridge delivers highest flow rate available in the market
- Single lever handle operation allows both volume and temperature control
- Pull/push type diverter allows a quick water flow switch from spout to hand shower or vice versa.
- Dual inlet ports – 1/2" CxC soldering & 3/4" NPT thread to ensure high flow rate
- Test plugs are supplied for on-site pressure testing.
- Trim set can be installed separately above the deck.
- 3 hole 6"-16" widespread installation
- Trim parts, cartridge, diverter and shower hose can be serviced above the mounting deck without touching rough-in valves.

Flow Rate

- 13 gpm (49L/min) @ 60 psig for spout
- 2.0 gpm @ 60 psig for hand shower

Finish

- CP (Polished Chrome)
- PVD-BN (PVD-Brushed Nickel)

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Single Lever Roman Tub Rough-in with Diverter Model: F2003B

