

SPECIFICATIONS

Customer Service: 1-800-460-7019
www.fluidfaucets.com

Specifications

- Heavy forged brass construction for durability and reliability
- Pressure balancing ceramic cartridge ensures anti-scald operation and life-long trouble-free service
- German made Fluhs brass ceramic 3-way diverter cartridge
- Single lever handle operation allows both volume and temperature control
- Max-temperature limit stop for added safety
- Integral stop valves for easy maintenance
- Dual inlet and outlet ports – 1/2" CxC soldering & 1/2" NPT thread
- Adjustable installation depth from 2-3/8" (60mm) to 3-1/8" (79mm)
- Mud guard is provided to help protect valve from dust and debris during installation
- Bubble level is attached to mud guard for easy and level installation
- Compliant to Cal Green requirement with a minimum transitional flow
- A wide selection of complimentary trims are sold separately
- For system with sharing: requires pressure balancing valve F1003B-SHARE

Flow Rate

- 5.5 gpm @ 60 psig

Finish

- Brass

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Pressure Balancing Valve with 3 Way Diverter Model: F1003B

