SPECIFICATIONS

Customer Service: 1-800-460-7019 www.fluidfaucets.com

Sustainable Solutions

Specifications

- Heavy brass construction for durability and reliability
- Single lever handle operation allows both volume and temperature control
- Tub spout can be either fixed squarely or swiveled into a desired position by $\pm 70^{\circ}$ in order to provide an easy access to bath tub.
- Pull/push type diverter allows a quick water flow switch from spout to hand shower or vise versa.
- Rough-in valve can be installed separately
- Trim parts can be serviced above the mounting deck without touching rough-in valves.
- 3 hole 6"-16" widespread installation
- Requires Single Handle Deck Mount Tub Filler Roughin with Diverter F2003B which is sold separately

Flow Rate

- 13 gpm (49L/min) @ 60 psig for spout
- 2.0 gpm @ 60 psig for hand shower

Finish

- CP (Polished Chrome)
- PVD-BN (PVD Brushed Nickel)


Codes and Standards


- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

Warranty

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial





fluid Quad Series **Single Handle Deck Mount Tub** Filler Trim Set with Hand Shower Model: F1613T







[25mm]



611/16"

