Sustainable Solutions

**Customer Service: 1-800-460-7019** 

www.fluidfaucets.com

# **Specifications**

- Heavy brass construction for durability and reliability
- Dual handle operation allows both volume and temperature control.
- German made Fluhs ceramic cartridge ensures life long trouble free service
- Pull/push type diverter allows a quick water flow switch from spout to hand shower or vice versa.
- Rough-in valve can be installed separately
- Trim parts can be installed and serviced above the mounting deck without touching rough-in valves.
- Stainless steel flexible connection for 6" to 16" wide installation
- Requires dual handle roman tub rough-in with diverter F2005B which is sold separately

### Flow Rate

- 15 gpm (56L/min) @ 60 psig for spout
- 1.8 gpm @ 60 psig for hand shower

#### **Finish**

- CP (Polished Chrome)
- PVD-BN (PVD Polished Nickel)

# **Codes and Standards**

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed (Pending)

## Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Symmetry Series

Four Piece Roman Tub Trim Set

**Model:** F1713T with Lever Handles **Model:** F1713XT with Cross Handles















