

SSi

Date: Sept 2020

NO CLOG II

Easy Height Round Front Washdown Toilet

0.8 gpf (3.0 lpf) Single Flush HET

Round Front Bowl #301401

LH Lever Tank #301400

RH Lever Tank #301400-R



MaP®
PREMIUM
MaP 800g



HIGH EFFICIENCY TOILET
HET



NO CLOG II Easy Height Round Front Washdown Toilet

0.8 gpf (3.0 lpf) Single Flush HET

Round Front Bowl #301401

LH Lever Tank #301400

RH Lever Tank #301400-R



A modern concept washdown 0.8 gpf (3.0 lpf) easy height single flush high efficiency toilet (HET) featuring side lever activation providing substantial water saving compared to other HET standard toilets and smooth contours for easy cleaning. The bowl has been designed with a 12" (305mm) outlet rough-in. The tank incorporates a high performance barrel style flushing valve which has been specially developed with this bowl to ensure optimum flushing performance. Due to the substantial water saving benefits achieved by the 0.8 gpf (3.0 lpf) single flush system, this toilet is suitable for multi-purpose applications where water conservation is important.

MaP Score: MaP premium 800g

Carry Distance: Drain line carry distance 54 ft (16 m) average per cUPC test.

Bowl: Round front washdown bowl with box flushing rim.

Outlet: Floor mounted 12" (305mm) outlet connection.

Tank: SSI NO CLOG II 0.8 gpf (3.0 lpf) tank has a free fitting lid and is suitable for domestic and light commercial applications.

Weight: Round Front Bowl 55 lbs (25 kg) and Tank 29 lbs (13 kg)

Water Control Valve Standand Bottom Entry Tank -- available as left hand inlet and incorporates ultra quiet water control assembly.

Fixing: The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.

Seat: A slow closing seat is included: Code No. 326201W for round front bowl

Colors: White

Dimensions: All dimensions are in inches and millimeters and are subject to normal manufacturing variations. SSI pursues a policy of continuing improvement in design and performance of its products. The right is reserved to vary specifications without notice.

