

### Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3-function hand shower and slide rail with wall outlet
- Integral wall outlet uses the fluid speed connection
- Curved diverting tub spout with fluid speed connection
- Requires pressure balancing valve F1001B or F1001B-PEX or F1001B-PEX-W
- Valve and trim package are sold separately

### Finish

- MB (Matte Black)

### Flow Rate

- Hand shower 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

### Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

### Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

## fluid Quad Series Hand Shower and Tub Spout Trim Kit Model: F161214TMB

### Includes:

- |                 |                             |
|-----------------|-----------------------------|
| F1001TMB        | Sleeve Tube and Cap         |
| FP6001033MB-1PB | Square Cover Plate          |
| FP6016041MB     | Quad Handle                 |
| FA803MB         | Slide Rail with Wall Outlet |
| FP6001007MB     | 60" Shower Hose             |
| FP40130MB       | 3 Function Hand Shower      |
| FP6098034LMB    | Curved Diverting Tub Spout  |

