

## SPECIFICATIONS

### Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3-function hand shower and slide rail with wall outlet
- 8" square rain shower head and 3" ceiling shower arm
- Quad tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W OR
- Requires pressure balancing valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve package and trim package sold separately

### Finish

- MB (Matte Black)

### Flow Rate

- Shower head and hand shower 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

### Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

### Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

## fluid Quad Series Shower Head, Hand Shower and Tub Spout Trim Kit Model: F16322TMB

Includes:

- |                |                             |
|----------------|-----------------------------|
| F1001TMB       | Sleeve Tube and Cap         |
| FP801013MB     | Diverter Sleeve Tube        |
| FP601143MB-3PB | Square Cover Plate          |
| FP605752MB     | Square Diverter Handle      |
| FP6016041MB    | Quad Handle                 |
| FA803MB        | Slide Rail with Wall Outlet |
| FP40130MB      | 3 Function Hand Shower      |
| FP6001007MB    | 60" Shower Hose             |
| FP6016034MB    | Quad Tub Spout              |
| FP6021308MB    | 3" Ceiling Shower Arm       |
| FP6001150MB    | 8" Square Shower Head       |

