



SPECIFICATIONS

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 6" round shower head and 8" shower arm
- Curved diverting tub spout with slip fit connection
- Requires pressure balancing valve F1001B or F1001B-PEX or F1001B-PEX-W
- Valve package and trim package sold separately

Finish

MB (Matte Black)

Flow Rate


- Showerhead 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed


Warranty


- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.






O.D.7¹/₁₆" [180mm]







O.D.2³/₁₆" [56mm] O.D.⁷/₁₆" [11.8mm] O.D.1³/₄"

fluid Wisdom Series Shower Head and Tub Spout Trim Kit

Model: F281023TMB

Includes:

www.fluidfaucets.com

F1001TMB FP6001035MB-1PB FP6028341MB FP6016008MB FP6000350MB

FP6098034LMB

Customer Service: 1-800-460-7019

Sleeve Tube and Cap Round Cover Plate Wisdom Handle 8" Shower Arm 6" Round Shower Head

6" Round Shower Head Curved Diverting Tub Spout









