

SPECIFICATIONS

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3-function hand shower and slide rail with wall outlet
- 6" round shower head and 8" shower arm
- Pipe tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W OR
- Requires pressure balancing valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve package and trim package sold separately

Finish

- MB (Matte Black)

Flow Rate

- Shower Head and hand shower 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Wisdom Series Shower Head, Hand Shower and Tub Spout Trim Kit Model: F283215TMB

Includes:

| | |
|-----------------|-----------------------------|
| F1001TMB | Sleeve Tube and Cap |
| FP801013MB | Diverter Sleeve Tube |
| FP6001142MB-3PB | Round Cover Plate |
| FP605652MB | Round Diverter Handle |
| FP6028341MB | Wisdom Handle |
| FA802MB | Slide Rail with Wall Outlet |
| FP40130MB | 3 Function Hand Shower |
| FP6001007MB | 60" Shower Hose |
| FP6016008MB | 8" Shower Arm |
| FP6000350MB | 6" Round Shower Head |
| FP6057034MB | Pipe Tub Spout |

