

SPECIFICATIONS

Customer Service: 1-800-460-7019
www.fluidfaucets.com

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 2-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3-function hand shower and slide rail with wall outlet
- 8" round rain shower head with 16" shower arm
- Round tub spout with quick connection
- Requires pressure balancing valve with shut off F1012B or F1012B-PEX or F1012B-PEX-W or pressure balancing valve with sharing F1012B-SHARE or F1012B-SHARE-PEX or F1012B-SHARE-PEX-W
- Valve package and trim package sold separately

Finish

- MB (Matte Black)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Hand shower 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Warranty against material and manufacturing defects for residential use. 5 year limited warranty on black finish.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Citi Series Tub and Shower Trim Kit Model: F243024TMB

Includes

- | | |
|-----------------|---------------------------|
| F1001TMB | Sleeve Tub and Cap |
| FP801013MB | Diverter Sleeve Tube |
| FP6001142MB-3PB | Round Cover Plate |
| FP6024041MB | Citi Handle |
| FP605652MB | Round Diverter Handle |
| FP6002150MB | 8" Round Shower Head |
| FP6006008MB | 16" Shower Arm |
| FA802MB | Slide Rail w/ Wall Outlet |
| FP6055034MB | Round Tub Spout |
| FP6001007MB | 60" Shower Hose |
| FP40130MB | 3 Function Hand Shower |

