

## SPECIFICATIONS

Customer Service: 1-800-460-7019  
www.fluidfaucets.com

### Specifications

- Metal construction for durability and reliability
- Swivel spout with 140 or 360 degree rotation
- Pull down and retractable magnet system
- Kerox ceramic cartridge ensures life long trouble free service
- Single handle operation allows both volume and temperature control
- Quick and easy installation with quick hose connector
- Dual function spray head with spray and aerated flow
- Limited to flow rate of 1.8 gpm (6.8 lpm) at 60 psi
- Max deck thickness 1-3/4" (45mm) w/ spacer and 2-1/2" (63mm) w/o spacer
- 1-1/2" (38mm) single faucet hole drilling recommended
- 8" deck plate for 3-hole installation available and is sold separately

### Finish

- MB (Matte Black)

### Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- NSF61-9
- ADA
- IAPMO / cUPC Listed
- AB1953 California Lead Plumbing Law Certified

### Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

## fluid Pull Down Kitchen Faucet with Magnetic Spray Head Model: F827MB

