

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 2-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 5-function round shower head and 8" shower arm
- Oceanside tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1012B or F1012B-PEX or F1012B-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)
- PN (PVD Polished Nickel)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Oceanside Series Shower Head and Tub Spout Trim Kit

Model: F232305T

Includes:

F1001T
FP801013
FP6023041
FP605752
FP6001143-2PB
FP20100
FP6027008
FP6023034

Sleeve Tube and Cap
Diverter Sleeve Tube
Oceanside/Vancouver Handle
Square Diverter Handle
Square Cover Plate
5 Function Shower Head
8" Shower Arm
Oceanside/Vancouver Tub Spout

