fiuid Innovative fixtures for life **SPECIFICATIONS**

Customer Service: 1-800-460-7019 www.fluidfaucets.com

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3 -function hand shower and slide rail w/ wall outlet
- Wall outlet with fluid speed connection
- Square tub spout with fluid speed connection
- Requires pressure balancing valve F1012B or F1012B-PEX or F1012B-PEX-W
- Valve package and trim package sold separately

Finish

MB (Matte Black)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1

30-

[50mm]

2⁵/16"

- ADA
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

4-(1/2"-14NPT)

2¼"-2¹⁵/16" [57.5mm-75mm]

4%"

[118mm]

715/16

[202mm]

-14 NPT

2

5<u>1/8</u>'

[27mm]

1⁷/₈" [48mm] ŀ

[130mm]

27¹¹/₆" 703.1mm]

22%16

1<u>%</u>["


[40mm]

[65mm]

fluid Quad Series Hand Shower and Tub Spout Trim Kit Model: F162074TMB

Includes:

F1001TMB FP801013MB FP601143MB-2PB FP605752MB FP6016041MB FA803MB FP6001007MB FP40130MB FP6056034MB Sleeve Tube and Cap Diverter Sleeve Tube Square Cover Plate Square Diverter Handle Quad Handle Slide Rail with Wall Outlet 60" Shower Hose 3 Function Hand Shower Square Tub Spout



59¹/16" [1500mm]





Sustainable Solutions 8395 Riverbend Court, Burnaby, BC V3N 5E7, Canada



Sustainable Solutions