Customer Service: 1-800-460-7019 www.fluidfaucets.com

Sustainable Solutions

SPECIFICATIONS

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 2-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3 function hand shower and slide rail with wall outlet
- 8" square rain shower head and 16" shower arm
- Requires pressure balancing valve with shut off F1012B or F1012B-PEX or F1012B-PEX-W
- Requires pressure balancing valve with sharing F1012B-SHARE or F1012B-SHARE-PEX or F1012B-SHARE-PEX-W
- Valve package and trim package sold separately

Finish

MB (Matte Black)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Hand shower 1.8 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

30=

[200.5mm]

Warrantv

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

4-(1/2"-14NPT)

ar and ercial O.D.3¹⁵₁₆" O.D.3¹⁵₁₆" O.D.3¹⁵₁₆" O.D.3¹⁵₁₆" I18.5mm S9¹/₁₆" I18.5mm

fluid Quad Series Shower Head and Hand Shower Trim Kit

Model: F162025TMB

Includes:

F1001TMB Sleev FP801013MB Divert FP6001143MB-2PB Squar FP605752MB Squar FP6016041MB Quad FP6007108MB 16" Si FP6001150MB 8" Sqi FA803MB Slide FP40130MB Round FP6001007MB 60" Si

Sleeve Tube and Cap Diverter Sleeve Tube Square Cover Plate Square Diverter Handle Quad Handle

16" Shower Arm 8" Square Shower Head Slide Rail w/ Wall Outlet Round Hand Shower 60" Shower Hose



