

SPECIFICATIONS

Customer Service: 1-800-460-7019 www.fluidfaucets.com

Sustainable Solutions

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 6" square shower head and 8" shower arm
- Curved diverting tub spout with slip fit connection
- Requires pressure balancing valve F1001B or F1001B-PEX or F1001B-PEX-W
- Valve package and trim package sold separately

Finish

MB (Matte Black)

Flow Rate


- Showerhead 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig


Codes and Standards


- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed


Warranty


- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.














fluid Quad Series shower Head and Tub Spout Trim Kit

Model: F161022TMB

Includes:

F1001TMB FP6001033MB-1PB FP6016041MB FP6027008MB FP6000150MB FP6098034LMB Sleeve Tube and Cap Square Cover Plate Quad Handle 8" Shower Arm 6" Square Shower Hea

6" Square Shower Head Curved Diverting Tub Spout









