

### Specifications

- Metal construction for durability and reliability
- Pressure balancing with built-in 2-way diverter ceramic cartridge ensures anti-scald operation with lifelong trouble free service
- Single lever handle operation allows flow diverting and temperature control
- 4" square shower head and 8" shower arm
- Curved tub spout with slip fit connection, (includes removable escutcheon, not pictured)
- Requires pressure balancing valve F1002B or F1002B-PEX or F1002B-PEX-W
- Valve package and trim package sold separately

### Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)

### Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

### Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

### Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

## fluid Quad Series Shower Head and Tub Spout Trim Kit Model: F164112T

Includes

- |               |                       |
|---------------|-----------------------|
| F1001T        | Sleeve Tub and Cap    |
| FP6016041     | Quad Handle           |
| FP6001033-2PS | Square Cover Plate    |
| FP6027008     | 8" Shower Arm         |
| FP10130       | 4" Square Shower Head |
| FP6098035L    | Curved Tub Spout      |

