

SPECIFICATIONS

Customer Service: 1-800-460-7019
www.fluidfaucets.com

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3-function hand shower and slide rail with wall outlet
- 8" round brass shower head and 6" ceiling shower arm
- Utopia tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W OR
- Requires pressure balancing valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Polished Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower head and hand shower 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Utopia Series Shower Head, Hand Shower and Tub Spout Trim Kit Model: F183009T

Includes:

- F1001T
- FP801013
- FP601142-3PB
- FP605652
- FP6018041
- FA802
- FP40120
- FP6001006
- FP6031034
- FP6018008
- FP6002050

- Sleeve Tube and Cap
- Diverter Sleeve Tube
- Round Cover Plate
- Round Diverter Handle
- Utopia Handle
- Slide Rail with Wall Outlet
- 3 Function Hand Shower
- 60" Shower Hose
- Utopian Tub Spout
- 6" Ceiling Shower Arm
- 8" Round Shower Head

