fluid Innovative fixtures for life

Sustainable Solutions

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 2-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 5 function round shower head and 8" shower arm
- Wisdom tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1012B or F1012B-PEX or F1012B-PEX-W OR
- pressure balancing valve with sharing F1012B-SHARE or F1012B-SHARE-PEX or F1012B-SHARE-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.



fluid Wisdom Series Shower Head and Tub Spout Trim Kit Model: F282305T

Includes: F1001T FP801013 FP6028341 FP605652 FP6001142-2PB FP20100 FP6016008 FP6041034

Sleeve Tub and Cap Diverter Sleeve Tube Wisdom Handle Round Diverter Handle Round Cover Plate 5 Function Shower Head 8" Shower Arm Wisdom Tub Spout









Sustainable Solutions 8395 Riverbend Court, Burnaby, BC V3N 5E7, Canada

[65m



1/2-14NP

<u>1³′ıs"</u> [29.9mm]