fluid^{Innovative fixtures for life}

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3 function hand shower and slide rail with wall outlet
- 6" square shower head with 8" shower arm
- 8" square brass rain shower head and 3" ceiling shower arm
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W OR
- Requires pressure balancing valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Polished Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower Head 1.8 gpm @ 60 psig
- Hand Shower 1.8 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

5-(1/2"-14NPT

2³/₈" - 3³/₁₆" [61mm-81mm

> 6" [152.2mm]




fluid Oceanside/Vancouver Series Shower Head, Hand Shower and Tub Spout Trim Kit Model: F233036T/F153306T

Includes: F1001T FP801013 FP6001143-3PB FP605752 FP6023041 FA803 FP40120 FP6001006 FP6021308 FP6027008 FP6020150 FP6001050


Sleeve Tube and Cap Diverter Sleeve Tube Square Cover Plate Square Diverter Handle Oceanside Handle Slide Rail with Wall Outlet 3 Function Hand Shower 60" Shower Hose 3" Ceiling Shower Arm 8" Shower Arm 6" Square Shower Head 8" Square Shower Head







25/16"



Sustainable Solutions