fluid Innovative fixtures for life SPECIFICATIONS

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control .
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 4" square shower head and 8" shower arm .
- 3 function hand shower and slide rail w/ wall outlet .
- Wall outlet with fluid speed connection .
- Requires pressure balancing valve F1012B or . F1012B-PEX or F1012B-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Chrome)
- **BN (PVD Brushed Nickel)**

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Hand shower 1.8 gpm @ 60 psig .

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

Customer Service: 1-800-460-7019 www.fluidfaucets.com


fluid Oceanside/Vancouver Series **Shower Head and Hand Shower Trim** Model: F232028T

Includes: F1001T FP801013 FP601143-2PB FP605752 FP6023041 FP6027008 FP6000150 FA803 FP6001006 FP40120

Sleeve Tube and Cap Diverter Sleeve Tube Square Cover Plate Square Diverter Handle Oceanside/Vancouver Handle 8" Shower Arm 6" Square Shower Head Slide Rail with Wall Outlet 60" Shower Hose **3 Function Hand Shower**







Sustainable Solutions