

SPECIFICATIONS

Sustainable Solutions

Customer Service: 1-800-460-7019 www.fluidfaucets.com

Specifications

- Metal construction for durability and reliability
- Pressure balancing with built-in 2-way diverter ceramic cartridge ensures anti-scald operation with life long trouble free service
- Single lever handle operation allows flow diverting and temperature control
- 6" square shower head and 8" shower arm
- Square tub spout with fluid speed connection
- Requires pressure balancing valve F1002B or F1002B-PEX or F1002B-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)

Flow Rate


- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig


Codes and Standards


- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed


Warranty


- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.













fluid Jovian Series Shower Head and Tub Spout Trim Kit

Model: F214109T

Includes: F1001T FP6021041 FP6001033-2PS FP6027008 FP6000150

FP6056034

Sleeve Tube and Cap Jovian Handle Square Cover Plate 8" Shower Arm 6" Square Shower Head Square Tub Spout







