fluid Innovative fixtures for life SPECIFICATIONS

Specifications

- Metal construction for durability and reliability
- . Pressure balancing with built-in 2-way diverter ceramic cartridge ensures anti-scald operation with life long trouble free service
- Single lever handle operation allows flow diverting and temperature control
- 8" square brass rain shower head and 16" shower arm .
- Square hand shower and wall mount support
- Square wall outlet with 1/2" NPT connection
- Requires pressure balancing valve F1002B or F1002B-PEX or F1002B-PEX-W
- Valve and trim packages are sold separately .

Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Hand shower 1.8 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

Customer Service: 1-800-460-7019 www.fluidfaucets.com

fluid Jovian Series **Shower Head and Hand Shower Trim Kit** Model: F214101T

Includes: F1001T FP6021041 FP6001033-2PS FP6007008 FP6001050 FP6081048 FP6001006 FP6004048 FP6001010

Sleeve Tube and Cap Jovian Handle Square Cover Plate 16" Shower Arm 8" Square Shower Head Square Wall Outlet 60" Shower Hose Square Hand Shower Hand Shower Holder



l	16" (402.5mm) 1/4" (7mm) 1/4" 1	15.58mm] 15.58mm]	
v _{j,i} " [15mm] 115 _{j,i} " [50mm]	1/2"-14NPT 1/4"	17.8" [48mm] [48mm] [100mm] [130mm] [130mm] [42.5mm]	1 ¹ .8" (28mm)
	1 ² /14" 39.5mm 	<u>165mm</u>]	L=60" [1500mm]



Sustainable Solutions