

### SPECIFICATIONS

Customer Service: 1-800-460-7019  
www.fluidfaucets.com

#### Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3-function hand shower and slide rail with wall outlet
- 6" square shower head and 8" shower arm
- Jovian tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W OR
- Requires pressure balancing valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve and trim packages are sold separately

#### Finish

- CP (Polished Chrome)
- BN (PVD Brushed Nickel)

#### Flow Rate

- Shower head and hand shower 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

#### Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

#### Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

## fluid Jovian Series Shower Head, Hand Shower and Tub Spout Trim Kit Model: F213027T

Includes:

- |               |                             |
|---------------|-----------------------------|
| F1001T        | Sleeve Tube and Cap         |
| FP801013      | Diverter Sleeve Tube        |
| FP6001143-3PB | Square Cover Plate          |
| FP605752      | Square Diverter Handle      |
| FP6021041     | Jovian Handle               |
| FA803         | Slide Rail with Wall Outlet |
| FP40120       | 3 Function Hand Shower      |
| FP6001006     | 60" Shower Hose             |
| FP6027008     | 8" Shower Arm               |
| FP6000150     | 6" Square Shower Head       |
| FP6016034     | Jovian Tub Spout            |

