fluid Innovative fixtures for life SPECIFICATIONS

Customer Service: 1-800-460-7019 www.fluidfaucets.com

Sustainable Solutions

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control .
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- . 3 function hand shower and slide rail w/ wall outlet
- Wall outlet with fluid speed connection .
- Square tub spout with fluid speed connection .
- Requires pressure balancing valve F1012B or F1012B-PEX or F1012B-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Chrome)
- **BN (PVD Brushed Nickel)**

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

[50mm]

ED)

2⁵/16"

2) [57 5

5¹¹/16" [145mm]

[202r

71/8" [181mm]

4-(1/2"-14NPT

fluid Oceanside Series Hand Shower and Tub Spout **Trim Kit** Model: F232074T

Includes: F1001T FP801013 FP601143-2PB FP605752 FP6023041 FA803 FP6001006 FP40120 FP6056034

O.D.3¹⁵/16" [100mm]

4¹¹/₁₆" [118.5mm]

59¹/16" [1500mm]

1¹⁵/16" [50mm]

11/16" [18mm]

____<u>1/16"</u>____

5½" [130mm

Sleeve Tube and Cap **Diverter Sleeve Tube** Square Cover Plate Square Diverter Handle Oceanside Handle Slide Rail with Wall Outlet 60" Shower Hose **3 Function Hand Shower** Square Tub Spout



