

caroma®

Date: April 2023

Supersedes all previous issues

Caravelle Smart Two Piece Easy Height Elongated with Side Lever Bowl #920102W Tank #920101W #920101W-R 1.28/0.8 gpf (4.8/3 lpf) Water Saving Dual Flush High Efficiency Toilet (HET) Two-Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet



**Caravelle Smart Two Piece
Easy Height Elongated with Side Lever
1.28/0.8 gpf (4.8/3L)
Dual Flush HET
Bowl #920102W Tank #920101W or #920101W-R**

**Two Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet**

Codes/Standards

ASME A112.19.2/CSA B45.1
EPA WaterSense
California Energy Commission (CEC)
ADA



A modern concept two piece toilet featuring a **1.28/0.8 gpf (4.8/3 lpf)** flush volume. **Caravelle Smart Two Piece Easy Height Elongated** left or right lever dual flush high efficiency toilet (HET) is designed to provide a seat height between 17" to 19" (432 to 482mm) measured to the top of the toilet seat for disabled persons. The versatility of the **Caravelle Smart Two Piece Easy Height Elongated** toilet makes it ideal for able bodied, ambulant persons with disabilities or for wheelchair users. Design with smooth rounded contours and a concealed outlet for easy cleaning. **Important:** The Caravelle Smart Two Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

- Toilet:** Caravelle Smart Two Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3 lpf) dual flush box rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.
- Bowl:** Elongated washdown bowl with box flusing rim.
- Tank:** The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications. Push down side lever for full flush (1.28 gpf / 4.8 lpf) and pull up side lever for reduced flush (0.8 gpf / 3 lpf). Tank with a right hand lever is available.
- Water Control Valve:** **Standard Bottom Entry** -- available as left hand inlet which incorporates a super quiet water control assembly. Internal overflow only.
- Weight:** 110 lbs (50.0 kg).
- Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system.
- Seat:** The soft close elongated seat is included: Code No. 326202W
- Colors:** White.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Top view dimensions: 6-7/8" (175mm) tank width, 13-1/16" (20mm) tank depth, 5-1/2" (140mm) seat hole diameter, 18-3/4" (475mm) bowl length, 14-1/8" (360mm) bowl width, 29-1/2" (750mm) total height, 21-1/4" (540mm) bowl depth.

Side view dimensions: 10-3/4" (272mm) tank width, 21-1/4" (540mm) bowl depth, 18" (455mm) to top of seat, 11" (280mm) seat height, 3" (50mm) seat depth, 10" (255mm) rough-in, 12" (305mm) rough-in.

Front view dimensions: 16-1/2" (420mm) bowl height, 30-3/4" (780mm) approx. total height, 216 mm (8-1/2") base width, 46mm (1 3/4") angle stop location.

Caravelle Smart Two Piece Easy Height Elongated Toilet:		Code No.
LH Tank	Left Side Lever	920101W
RH Tank	Right Side Lever	920101W-R
Bowl	ELG & EH	920102W

Map Test Score 1000g

Meets EPA Criteria
Certified by IAPMO RST

HIGH EFFICIENCY TOILET
HET

Note: All height dimensions to underside of closet bowl. Make allowance for bedding.

Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking.