# fluid

### **Specifications:**

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- > Valve and trim packages are sold separately
- → Requires the fluid F1001B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

### **Components:**

F1001T	Sleeve Tube and Cap
FP6024041	Citi Handle
FP6001035-1PB	Round Cover Plate
FP6098034L	7.5" Curved Diverting Tub Spout
FP6016008	8" Shower Arm
FP6000350	6" Round Shower Head

## Citi Curved Diverting Tub Spout & 6" Shower Head Trim Kit

F241023T







#### **Features:**



Requires F1001B



**Bubble Level** 



Integral Stops




Slip Fit Connection

Polished Chrome (CP), Brushed Nickel (BN) and Matte Black (MB)


# fluid


### **Technical Drawing**


F241023T





















### **Warranty:**

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

#### **Codes and Standards:**

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed EPA Watersense Listed

#### Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: **F241023T-15**