fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- > Valve and trim packages are sold separately
- Requires the fluid F1001B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6028341	Wisdom Handle
FP6001035-1PB	Round Cover Plate
FP40120	3 Function Hand Shower*
FP6012047	Round Wall Outlet Holder
FP6001006	60" Shower Hose*

 Matte black uses an FP6001007MB Shower Hose & FP40130MB 3 Function Hand Shower

Wisdom 3 Function Hand Shower Only Trim Kit, (Round Holder)

F281205T





Polished Chrome (CP), Brushed Nickel (BN) and Matte Black (MB)

Features:



Requires F1001B



Bubble Level



Integral Stops




Speed Connect


F281205T July 2023

fluid

Technical Drawing

F281205T



















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed EPA Watersense Listed

Flow Rate:

Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Hand Shower @ 1.5 gpm: **F281205T-15**