## fluid

### **Specifications:**

- → Metal construction for durability and reliability
- Pressure balancing volume control with 3-way, two handle diverting
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- Requires the fluid F1003B pressure balancing valve, (sold separately and available with shut off or \*\*sharing in solder, PEX and PEX-W.)

### **Components:**

F1001T	. Sleeve Tube and Cap
FP6028341	· •
FP801013	. Diverter Sleeve
FP605752	. Diverter Handle
FP6001143-3PB	. Cover Plate
FP6002050	.8" Brass Showerhead
FP40120	. 3 Function Hand Shower
FA802	. Slide Bar With Integral Outlet
FP6001006	. 60" Shower Hose
FP6041034	. Wisdom Tub Spout

\*\*sharing available where allowed by code

Kit with Alternate Handle: F283024T-AR



### **Features:**



Requires F1003B



Bubble Level



Integral Stops



Speed Connect

### Wisdom Tub, 3 Function Hand Shower and 8" Rain Shower Kit

F283024T





Available in Polished Chrome (CP) and Brushed Nickel (BN)

# fluid

### **Technical Drawing**

F283024T





15%" [42mm]









### **Warranty:**

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

### **Codes and Standards:**

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

#### Flow Rate:

Shower Head 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Hand Shower & @ 1.5 gpm: **F283024T-15**