Innovative fixtures for life.

fluid

Citi Curved Tub Spout & 4" Shower Trim Kit (F1002B)

F244107T







Specifications:


- ➔ Metal construction for durability and reliability
- Pressure balancing, single handle, 2-way diverting with temperature control
- ➔ Max-temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- ➔ Valve and trim packages are sold separately
- Requires the fluid F1002B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)
- → ADA Compliant

Components:

F1001T	Sleeve Tube and Cap
FP6024041	. Citi Handle
FP6001035-2PS	Round Cover Plate
FP6098035L	7.5" Curved Tub Spout
FP6016008	8" Shower Arm
FP10120	4" Round Shower Head







Slip Fit Connection

Polished Chrome (CP), Brushed Nickel (BN) and Matte Black (MB) $\,$

fluid by Sustainable Solutions



fluid

Technical Drawing

1/2-14NP⁻ <u>3/8"</u> [10mm] <u>O.D.2¹/2"</u> [63.5mm] O.D.¹ %。" [20.6mm] 1/2"-14NPT <u>O.D.1%</u>" [48mm] ¹⁄4" [6mm] ¹¹/₁₆" [18mm] 2¹/₄"-3¹/₁₆" [57mm-77mm] 4¹/₁₆" [119mm] <u>O.D.7¹/₁₆"</u> [180mm] <u>O.D.2¹³/16</u> [72mm] 7¹¹/16" [194.7mm] .8mm <u>%</u>" [8mm] <u>O.D.2³/16" [55.9mm]</u> 67. <u>O.D.1¾"</u> [45mm]

<u>9%16"</u> [242.4mm]

Warranty:

đ

And End of the Second

NSE Certified to NSF/ANSI 61

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.


Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @1.5 gpm: F244107T-15



F244107T