

## Pull Down Kitchen faucet






F829MB

### Specifications:

- Metal construction
- Angular swivel spout with 360 degree or 140 degree rotation with supplied stop
- Kerox ceramic cartridge ensures lifelong trouble free service
- Single handle operation, allows both volume and temperature control
- Quick and easy installation with quick hose connector
- Dual function spray head with spray and aerated flow
- Limited to a flow rate of 1.5 gpm (5.7 lpm) at 60 psi
- Maximum deck thickness of 1 - 3/4" with spacer and 2-1/2" (63 mm) without spacer
- 1-1/2" (38 mm) faucet hole size for drilling is recommended
- 8" deck plate for 3 hole installation is available and sold separately
- ADA Compliant




### Features:

-  360 Degree Rotation with 140 Degree Lock
-  Dual Spray Kitchen Faucet
-  Ceramic Disk Cartridge
-  Pull Down Kitchen Spout
-  Metal construction

Matte Black (MB)

## Technical Drawing

F829MB



### Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

### Codes & Standards:

ANSI/ASME A112.18.1

CSA B125.1

NSF/ANSI/CAN 61: Q < 1

NSF / ANSI / CAN372

IAPMO / cUPC Listed

EPA Watersense Listed

ADA Compliant

### Flow Rate:

1 gpm, (3.8 lpm), @ 60 psig