# fluid

### **Specifications:**

- Metal construction
- Pressure balancing volume control with 3-way, two handle diverting
- Maximum temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- → Requires the fluid F1003B or F1013B pressure balancing valve, (sold separately and available with shut off or \*\*sharing in solder, PEX and PEX-W, F1960 Expansion PEX)

### **Components:**

F1001TBG	Cartridge Sleeve
FP6019041BG	Cartridge Handle
FP801013BG	Diverter Sleeve
FP605652BG	Diverter Handle
FP6001142-3PB	Cover Plate
FP6002050BG	8" Brass Showerhead
FP6006008BG	16" Shower Arm
FP40120BG	3 Function Hand Shower
FA802BG	Slide Bar With Integral Outlet
FP6001006BG	60" Shower Hose
FP6095035BG	Slimline Tub Spout

\*\*sharing available where allowed by code

Kit with Alternate ADA Diverter Handle: F193025TBG-AS



### Features:



Requires F1003B 🛛 📼 But

Bubble Level

Speed Connect

fluid by Sustainable Solutions

Integral Stops

## Yaletown Tub, Rain Shower & Hand Shower on Slide Bar Trim Kit

# F193025TBG



PVD Brushed Gold (BG)

F193025TBG November 2023

# fluid

### **Technical Drawing**

16" [406.4mm] O.D.2½" [63.5mm] 3/8" [10mm] O.D.4" [100mm] ╞ O.D.8" 125.7 [201mm] 5-(1/2"-14NPT) O.D.7<sup>1</sup>/<sub>16</sub>" [180mm] 27<sup>1</sup>½。" 703.2mm] 4<sup>1</sup>/<sub>16</sub>" [118.5mm] O.D.1½" [29mm] 74 [6mm] b. / R¾" [R10mm] 0.D.1<sup>15</sup>/<sub>6</sub> 2<sup>3</sup>/<sub>8</sub>" -3<sup>3</sup>/<sub>16"</sub> [61mm-81mm] <u>1%<sub>16</sub>" [34mm]</u> 4½" [104mm] 60" [1500mm] ED) 4<sup>3</sup>/<sub>4</sub>" [120.6mm] <u>O.D.1<sup>7</sup>/8"</u> [48mm] 1/2"-14 NPT <u>2%16"</u> [65mm] 2<sup>5</sup>/<sub>16</sub>" [59mm] 2<u>%</u>6" [65mm] 7<sup>15</sup>/<sub>16</sub>" [202mm] \_\_\_\_\_\_\_\_\_\_ [42mm 7<sup>1</sup>/<sub>8</sub>" [180.5mm]

Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO/cUPC Listed, EPA Watersense Listed

#### Warranty:

JPC .

**NSF** Certified to NSF/ANSI 61

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

## **Kit Variations:**

Kit with ADA diverter handle: F193025TBG-AR

Kit with square style cover plate & diverter handle: F193025TBG-S

#### **Flow Rate:**

Shower Head 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Hand Shower @ 1.5 gpm: F193025T-15



