# fluid

# **Specifications:**

- → Metal construction for durability and reliability
- Pressure balancing volume control (non-diverting)
  Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- Requires the fluid F1001B pressure balancing valve, (sold separately and available with shut off in solder, PEX and PEX-W.)


### **Components:**

| F1001T        | Cartridge Sleeve |
|---------------|------------------|
| FP6016041     | Quad Handle      |
| FP6001033-1PB | Cover Plate      |
| FP6056034     | Cubed Tub Spout  |

# Quad Square Tub Spout Only Trim Kit

F161313T





#### **Features:**



Requires F1001B



**Bubble Level** 



 $Integral\,Stops$ 





Speed Connect

Polished Chrome (CP), Brushed Nickel (BN) and Matte Black (MB)

# **Technical Drawing**

F161313T



















## **Warranty:**

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

## **Codes and Standards:**

ANSI/ASME A112.18.1, CSA B125.1, IAPMO/cUPC Listed, EPA Watersense Listed

#### Flow Rate:

Tub Spout 4.5 gpm @ 60 psig