fluid

Specifications:

- → Metal construction for durability and reliability
- Pressure balancing volume control with 2-way two handle diverting
- ➔ Max-temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- Requires the fluid F1012B pressure balancing valve, (sold separately and available with shut off or **sharing in solder, PEX and PEX-W.)

Components:

F1001T	. Cartridge Sleeve
FP6016041	. Quad Handle
FP801013	. Diverter Sleeve
FP605752	. Diverter Handle
FP6001143-2PB	. Cover Plate
FP6027008	. 8″ Shower Arm
FP6000150	. 6″ Shower Head
FP6004048	. Square Hand Shower
FA104	. Slide Bar
FP6001047	. Wall Outlet
FP6001006	. 60" Shower Hose

**sharing available where allowed by code

Features:

😗 Requires F1012B

Integral Stops

📼 Bubble Level

Speed Connect

Available in Polished Chrome (CP) and Brushed Nickel (BN)

Quad Square 6" Shower Head & Hand Shower Trim Kit

F162309T



fluid by Sustainable Solutions

F162309T November 2023

fluid

Technical Drawing

<u>9¾₁₆"</u> [232.7mm] <u>2%₁₆" [65mm]</u> 3/8" [10mm] O.D ¹³/₁₆" [20.6mm] 1¾" [35mm] σ <u>%₁₆" [15mm]</u> 6" [152.4mm] 5-(1/2"-14NPT) 5¹/8" [130mm] ____¼₀" [27mm] 26%" [670mm] 31/6" 80mm ŀ 4¹/₁₆" [118.5mm] 2³%" -3³/16" [61mm-81mm] <u>2⁵⁄₁₆" [58.9mm]</u> 2' 5" [125.2mm] 2¼" [57.5mm] <u>2%16"</u> [65mm] 1½" [28mm]

Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed, EPA Watersense Listed

Warranty:

JP0

Certified to

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Kit Variations:



Kit with alternate ADA diverter handle: **F162309T-AS**

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Shower Head & Hand Shower @ 1.5 gpm: **F162309T-15**

F162309T November 2023

