fluid

Specifications:

- → Metal construction for durability and reliability
- Pressure balancing volume control with 2-way two handle diverting
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- > Valve and trim packages are sold separately
- Requires the fluid F1012B pressure balancing valve, (sold separately and available with shut off in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6021041	Jovian Handle
FP801013	Diverter Sleeve
FP605752	Diverter Handle
FP6001143-2PB	Cover Plate
FP6027008	8" Shower Arm
FP6000150	6" Shower Head
FP6056034	Cubed Tub Spout

Jovian Square Tub & 6" Shower Head Trim Kit

F212250T







Features:



Requires F1012B



Bubble Level



Integral Stops





Speed Connect


Available in Polished Chrome (CP) and Brushed Nickel (BN)


Technical Drawing

F212250T




















Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed, EPA Watersense Listed

Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Kit Variations:



Kit with alternate ADA diverter handle: **F212250T-AS**

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: **F212250T-15**