fluid


Specifications:


- → Metal construction for durability and reliability
- → Pressure balancing volume control with 2-way two handle diverting
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- Requires the fluid F1012B pressure balancing valve, (sold separately and available with shut off in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6023041	Oceanside/Vancouver Handle
FP801013	Diverter Sleeve
FP605752	Diverter Handle
FP6001143-2PB	Cover Plate
FP40120	Hand Shower
FA803	Slide Bar
FP6001006	60" Shower Hose
FP6054034	Sloped Tub Spout

Features:





Integral Stops

Speed Connect

Oceanside/Vancouver Tub Spout and Hand Shower Trim Kit


F232254T



Available in Polished Chrome (CP) and Brushed Nickel (BN)

Technical Drawing

F232254T



Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed, EPA Watersense Listed

Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Kit Variations:



Kit with alternate ADA diverter handle: **F232254T-AS**

Flow Rate:

Tub Spout 4.5 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Hand Shower @ 1.5 gpm: **F232254T-15**