fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control with 2-way two handle diverting
- → Maximum temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- → Requires the fluid F1012B pressure balancing valve, available in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6028341	Wisdom Handle
FP801013	Diverter Sleeve
FP605652	Diverter Handle
FP6001142-2PB	Cover Plate
FP6016008	8" Shower Arm
FP6000350	6" Shower Head
FP6057034	Pipe Tub Spout

Wisdom Tub & 6" Shower Head Trim Kit

F282244T








Features:








Speed Connect

Polished Chrome (CP), Brushed Nickel (BN) and Matte Black (MB)


fluid


Technical Drawing


F282244T













Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO/cUPC Listed, EPA Watersense Listed

Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Kit Variations:



Kit with alternate ADA diverter handle: **F282244T-AR**

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: **F282244T-15**