fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing single handle 2-way Diverting
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- > Valve and trim packages are sold separately
- → Requires the fluid F1002B pressure balancing valve, (sold separately and available with shut off in solder, PEX and PEX-W.)

Components:

F1001TMB	Cartridge Sleeve
FP6024041MB	Citi Handle
FP6001035MB-2PS	Cover Plate
FP6016008MB	8" Shower Arm
FP20100MB	5 Function Shower Head
FP6055035MB	Round Tub Spout

Citi Tub & 5 Function Shower Head Trim Kit

F244104TMB







Features:



Requires F1002B



Bubble Level



Integral Stops




Slip Fit Tub Spout

Available in Matte Black


fluid


Technical Drawing


F244104TMB



















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed, EPA Watersense Listed

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: **F244104TMB-15**