fluid

Specifications:

- ➔ Metal construction for durability and reliability
- Pressure balancing volume control (non-diverting)
- → Max-temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- Requires the fluid F1001B pressure balancing valve, (sold separately and available with shut off in solder, PEX and PEX-W.)

Components:


F1001TMB	Cartridge Sleeve
FP6016041MB	Quad Handle
FP6001033MB-1PB	Square Cover Plate
FP933001MB	Switch Slide Bar
FP900208MB	8″ Switch Shower Arm
FP6000150MB	6" Shower Head
FP40130MB	3 Function Hand Shower
FP6001007MB	60" Shower Hose
FP6098034LMB	Curved Diverting Tub Spout


Quad Switch 6" Shower Head & Hand Shower Trim Kit

F161221TMB



Features:





Speed Connect Slide Bar

Available in Matte Black

Slip Fit Tub Spout

Integral Stops

fluid by Sustainable Solutions

F161221TMB January 2024

fluid

Technical Drawing

8¾" [221.6mm] O.D.1" [25mm] O.D.4⁵/₁₆" [110mm] 2"-14NP 4¹¹/₁₆" 118.5mm] O.D.1" [25mm] Ъ 4¹⁵/₆" 125mm] <u>/4</u>" [6mm] 4-(1/2"-14NPT) 7½" 190mm 21/4"-31/16" [57mm-77mm] 1%" 4%" [124mm 5½" [130mm] 3½6" 78.6mm] 0.D.2³ [56mr 0.D.7/16 6¹³/16" O.D.1¾" [45mm]

Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1, CSA B125.1, IAPMO/cUPC Listed, EPA Watersense Listed

Flow Rate:

Hand Shower 1.8 gpm @ 60 psig Shower Head 1.8 gpm @ 60 psig Tub spout 4.5 gpm @ 60 psig Low Flow Alternative: Hand Shower & Shower Head @ 1.5 gpm: F161221TMB-15

pg 2.





NSE Certified to NSF/ANSI 61

