fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing single handle 2-way diverting
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- > Valve and trim packages are sold separately
- → Requires the fluid F1002B pressure balancing valve, (sold separately and available with shut off in solder, PEX and PEX-W.)

Components:

| F1001TMB | Cartridge Sleeve |
|-----------------|--------------------|
| FP6016041MB | Quad Handle |
| FP6001033MB-2PS | Square Cover Plate |
| FP6027008MB | 8" Shower Arm |
| FP6000150MB | 6" Shower Head |
| FP6098035LMB | Curved Tub Spout |

Quad Tub and 6" Shower Head Trim Kit

F164211TMB





Features:



Requires F1002B



Bubble Level



Integral Stops



Slip Fit Tub Spout





Available in Matte Black


fluid


Technical Drawing


F164211TMB




















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed, EPA Watersense Listed

Flow Rate:

Tub spout 4.5 gpm @ 60 psig Shower Head 1.8 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: **F164211TMB-15**