# fluid

## **Specifications:**

- → Metal construction for durability and reliability
- Pressure balancing volume control with 2-way two handle diverting
- ➔ Max-temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- > Valve and trim packages are sold separately
- Requires the fluid F1012B pressure balancing valve, (sold separately and available with shut off or \*\*sharing in solder, PEX and PEX-W.)

## **Components:**


F1001TMB	Cartridge Sleeve
FP6016041MB	Quad Handle
FP605752MB	Square Diverter Handle
FP801013MB	Diverter Sleeve Tube
FP6001143MB-2PB	Square Cover Plate
FP6001150MB	6" Square Shower Head
FP6007108MB	8" Shower Arm
FP6056034MB	Cubed Tub Spout

#### \*\*sharing available where allowed by code

### Features:

**ਪ੍ਰੈ** Requires F1012B

Integral Stops



Speed Connect

Quad Tub and 6" Shower Head Trim Kit

# F162026TMB







Available in Matte Black

fluid by Sustainable Solutions

F162026TMB January 2024

# fluid

### **Technical Drawing**

## 8%/16" [217.7mm \_\_\_2%/<sub>16</sub>" [65mm] 0.D.<sup>1</sup>¾," [20.6mm] 5<sup>1</sup>⁄8" [130mm] 4-(1/2"-14NPT) 31/%" [80mm] □1/16" [27mm] [125mm 2<sup>1</sup>/<sub>4</sub>"-2<sup>1</sup>5/<sub>16</sub> [57.5mm-75mm] 45/8'' [118mm] /2"-14 NP1 7<sup>1</sup>5/16" **2**<sup>2</sup>/16" [202mm] 1%16" 7<sup>1</sup>/8" [181mm]

Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed, EPA Watersense Listed

#### Warranty:

30

**NSF** Certified to NSF/ANSI 61

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

### **Kit Variations:**



Kit with alternate ADA diverter handle: F162026TMB-AR

### **Flow Rate:**

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: F162026TMB-15

