🕈 Caroma

design for life...

Specifications

- Vitreous China Dual Flush High Efficiency Toilet (HET)
- Elongated washdown bowl with box flushing rim.
- \rightarrow Designed to provide a seat height of 17 $\frac{1}{2}$ (445mm) measured to the top of the toilet seat.
- Smooth contours and a concealed trapway for easy cleaning
- The toilet is suitable for multi-purpose applications, including → those where water conservation is important
- A 326202W soft close elongated seat is included.
- Left Lever Toilet: 987200 Right Lever Toilet: 987200-R
- Weight: 103 lbs (47.0 kg)

Outlet:

Floor mounted. Connection to waste outlet requires the offset plastic Caroma Smart Connect outlet connector and is adaptable for 10" (255mm) to 12" (305mm) rough-in.

Tank:

The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications. Push down side lever for full flush (1.28 gpf / 4.8 lpf) and pull up side lever for reduced flush (0.8 gpf / 3 lpf).

Water Control Valve:

Standard Bottom Entry Tank - available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.

Fixing:

The one piece toilet is fixed to the floor with the Smart Connect Offset Adapter. Bowl is to be bonded to the floor with an approved silicon caulking.

Features:



Smart Connect Included



Skirted Bowl

One Piece



Soft Closing Seat

Sydney Smart One Piece Easy **Height Elongated Lever Toilet**

987200(-R)


Flush Volume: 1.28/0.8 gpf (4.8/3 lpf)

Technical Drawing & Certifications

All dimensions are in inches and millimeters and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Closet bowl fixing: The closet bowl should be sealed with an approved silicon caulking.


Smart Glaze "



13/16" (20mm) 7-1/2" (185mm) 5-1/2" (140mm) 29-15/16' (760mm) 18-1/2" (470 mm)14-1/8" (360mm) Angle Stop Location (770mm) approx. (420mm 30-3/8" 16 - 1/20



987200 (-R)



Warranty:

Two year limited warranty

Caroma plumbing products are warranted to be free of defects in material and workmanship for two years after their initial purchase. This limited warranty applies only to the original purchaser and installation of these products. In the event of a limited warranty claim, proof of purchase from an authorized reseller will be required.

Important:

The Sydney Smart II One Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

fluid by Sustainable Solutions

987200(-R) March 2024