fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control with 2-way two handle diverting
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- Requires the fluid F1012B pressure balancing valve, (sold separately and available with shut off in solder, PEX and PEX-W.)

Components:

F1001TMB	Cartridge Sleeve
FP6016041MB	Quad Handle
FP605752MB	Square Diverter Handle
FP801013MB	Diverter Sleeve Tube
FP6001143MB-2PB	Square Cover Plate
FP20100MB	5 Function Shower Head
FP6027008MB	8" Shower Arm
FP6056034MB	Cubed Tub Spout

Quad Tub & 5 Function Shower Head Trim Kit

F162212TMB





Features:



Requires F1012B



Bubble Level



Integral Stops



Speed Connect Tub Spout





Available in Matte Black


fluid


Technical Drawing

F162212TMB





















Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed, EPA Watersense Listed

Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Kit Variations:



Kit with alternate ADA diverter handle: **F162212TMB-AR**

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: **F162212TMB-15**