

fluid

Innovative fixtures for life

SPECIFICATIONS

Customer Service: 1-800-460-7019
www.fluidfaucets.com

SSITM
SUSTAINABLE
SOLUTIONS
INTERNATIONAL

Specifications

- Heavy brass construction for durability and reliability
- High arc spout design with 360 degree rotation
- Italy made Hydroplast ceramic cartridge ensures life long trouble free service
- Single handle operation allows both volume and temperature control
- Dual function spray head with spray and aerated flow
- Limited to flow rate of 2.2 gpm (8.3 lpm) at 60 psi
- Stainless steel flex supplies with 3/8" comp connection
- Max deck thickness 1-1/2" w/ spacer and 2-1/8" w/o spacer
- Min 3-1/8" distance from back splash wall
- 1-1/2" single faucet hole drilling recommended
- Available 8" deck plate for 3 hole installation

Finish

- CP (Polished Chrome)
- PVD-BN (coming soon)

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- NSF61-9
- ADA
- IAPMO / cUPC Listed
- AB1953 California Lead Plumbing Law Certified

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Pull Down Kitchen Faucet Model: F821

