

### **Specifications:**

- → Metal construction for durability and reliability
- → Pressure balancing with 2-way, single handle diverting and temperature control
- → Maximum temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Requires the fluid F1002B or F1042B pressure balancing valve, (available in solder, PEX and PEX-W.)
- → ADA compliant

#### **Components:**

F1001T	Sleeve Tube and Cap
FP6024041	Blade Handle
FP6001035-2PS	Round Cover Plate
FP20100	5 Function Shower Head
FP6016008	8" Shower Arm
FP6055035	Round Tub Spout

# Citi Tub & 5 Function Shower Trim Kit, (Single Handle)

F244104T







#### **Features:**



Requires non-diverting F1002B or F1042B valve



Integral Stops



Bubble Level



Slip fit spout



ADA

Polished Chrome (CP) , Brushed Nickel (BN) & Matte Black (MB)

fluid by **Sustainable Solutions** 

**Email**: help@sustainablesolutions.com


**Toll free:** 1-800-460-7019




## fluid


#### **Technical Drawing**


## F244104T



















Codes and Standards: ANSI/ASME A112.18.1, CSA B125.1, IAPMO / cUPC Listed

### **Warranty:**

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

#### **Kit Variations:**

Kit with square style cover plate & diverter handle: F244104T-S

#### Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: F244104T-15

fluid by Sustainable Solutions

**Email**: help@sustainablesolutions.com

**Toll free:** 1-800-460-7019



F244104T February 2025