

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control with 2-way single handle diverting
- → Maximum temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- → Requires the fluid F1002B or the F1042B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)
- → ADA compliant

Components:

F1001T	Cartridge Sleeve
FP6024041	Blade Handle
FP6001035-2PS	Round Cover Plate
FP6016008	8" Shower Arm
FP6000350	6" Shower Head
FP6098035L	Curved Tub Spout

Citi Tub & 6" Shower Trim Kit (Single Handle)

F244109T







Features:



Requires 2-way diverting F1002B or F1042B valve



Integral Stops



Bubble Level



Speed Connect

Polished Chrome (CP), Brushed Nickel (BN) & Matte Black (MB)

F244109T February 2025

fluid by Sustainable Solutions

Email: help@sustainablesolutions.com


Toll free: 1-800-460-7019





Technical Drawing

F244109T














 $\textbf{Codes and Standards:} \ \, \texttt{ANSI/ASME} \, \, \texttt{A112.18.1}, \, \, \texttt{CSAB125.1}, \, \, \texttt{IAPMO/cUPC} \, \texttt{Listed} \, \,$

Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Kit Variations:

Kit with square style cover plate & diverter handle: F244109T-S

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: F244109T-15

F244109T February 2025

fluid by Sustainable Solutions

Email: help@sustainablesolutions.com

Toll free: 1-800-460-7019

