fluid

Specifications:

- → Metal construction for durability and reliability
- > Pressure balancing, single handle, 2-way diverting with temperature control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- Valve and trim packages are sold separately
- → Requires the fluid F1002B or F1042B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)
- → ADA Compliant

Components:

F1001T	Sleeve Tube and Cap
FP6024041	Blade Handle
FP6001035-2PS	Round Cover Plate
FP6055035	7.5" Round Tub Spout
FP6016008	8" Shower Arm
FP10120	4" Round Shower Head

Citi Curved Tub Spout & 4" Shower Trim Kit (F1002B)

F244116T







Features:



Requires non-diverting F1002B or F1042B valve



Integral Stops



Bubble Level




Slip Fit Connection

Polished Chrome (CP), Brushed Nickel (BN) & Matte Black (MB)


fluid


Technical Drawing


F244116T



















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @ 1.5 gpm: **F244116T-15**