fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- > Valve and trim packages are sold separately
- → Requires the fluid F1001B or F1021B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001T	Sleeve Tube and Cap
FP6024041	Blade Handle
FP6001033-1PB	Square Cover Plate
FP10130	4" Square Shower Head
FP6027008	8" Shower Arm

Citi 4" Square Shower Only Trim Kit

F241220T





Features:



Requires non-diverting F1001B or F1021B valve



Integral Stops




Bubble Level


Polished Chrome (CP), Brushed Nickel (BN) & Matte Black (MB)



Technical Drawing

F241220T

















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

Flow Rate:

Shower Head 1.8 gpm @ 60 psig

Low Flow Alternative: Shower Head @1.5 gpm: **F241220T-15**