fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Valve and trim packages are sold separately
- → Requires the fluid F1001B or F1021B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001TMB	Sleeve Tube and Cap
FP6024041MB	Blade Handle
FP6001035MB-1PB	Round Cover Plate
FP6098034LMB	7.5" Curved Diverting Tub Spout
FP6016008MB	8" Shower Arm
FP6000350MB	6" Round Shower Head

Citi Curved Diverting Tub Spout & 6" Shower Head Trim Kit

F241023TMB







Features:



Requires non-diverting F1001B or F1021B valve



Integral Stops




Bubble Level

Matte Black (MB)


fluid


Technical Drawing

F241023TMB





















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

Flow Rate:

Shower Head 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head @1.5 gpm: **F241023TMB-15**