fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- Requires the fluid F1001B or F1021B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6018041	. Utopia Handle
FP6001035-1PB	Round Cover Plate
FP40120	3-Function Hand Shower
FA101	.Slide Bar
FP6082048	.Wall Outlet
FP6001006	60" Shower Hose

Utopia Hand Shower on FA101 Slide Bar Trim Kit

F181011T



Polished Chrome (CP) and Brushed Nickel (BN)

Features:

Requires non-diverting F1001B or F1021B valve		
O Integral Stops	Bubble Level	
Speed Connect		

F181011T March 2025

fluid

Technical Drawing

3

C C C

(NSE) Certified to NSF/ANSI 61 Adjustable 235/8 [600mm]

O.D.1"

Warranty:

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed **EPA Watersense Listed** ADA Compliant

Flow Rate:

Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Hand Shower @ 1.5 gpm: F181011T-15

F181011T March 2025

[25mm] O.D.7¹/₁₆" [180mm] 22 2¹⁄₄"-3¹⁄₁₆" [57mm-77mm] 24[\]/₆" [612mm] 1⁷/8" [48mm] 1/2"-14NPT 45/ 6" 35mm 4¹¹/₁₆" [119mm] 1³/₈" [35.5mm] O.D.113/16" [46.5mm] 2[%]/16" [65mm] 3/16" O.D.2%16 [4mm] [65mm] 1%16" [39mm]



O.D.3¹⁵/16" [100mm]

